


NOTE:

- 1.Specified failure load: 70kN.
- 2.Range of diameter of cable dia.:10.2-11.4mm.
- 3.Grip strength:95%RTS.
- 4.All ferrous parts are hot-dip galvanized.
- 5.All dimensions are in millimeters.
- 6.Applicable standard.(ISO 1461 IS 2486/IEC:61284).

7	1	GROUND WIRE	JDX70-2000	AL ALLOY	/
6	1	GROOVE CLAMP	JB-1	AL ALLOY	/
5	2	BOW SHACKLE	U-7	GALV.STEEL	70kN
4	1	PROLATE BOARD	PD-7	GALV.STEEL	70kN
3	1	THIMBLE	TC-7	GALV.STEEL	70kN
2	1	OUTER PREFORMED	ONY 1140 70-W	AL CLAD STEEL	/
1	1	INNER PREFORMED	ONY 1140 70-N	AL CLAD STEEL	/
ITEM	Q'TY	DESCRIPTION	TYPE	MATERIAL	Failure load

 Nantong Hongzhi Communication Equipment Co., LTD		Tension string for OPGW TYPE:ONY 1140 70	
Tolerance			
≤30mm	±1.5mm		
>30mm	±5%	DATE:2020-01-10	
MAX.	±10mm		
DRAWING	L.Z.G	DRAWING NO. ONY 1140 70	Version A
VERIFY	ZH.J		
RATIFICATION	ZH.J		