


NOTE:

- 1.Specified failure load:70kN.
- 2.Range of diameter of cable dia.:10.1-11.0mm.
- 3.Grip strength: $\geq 14\%$ RTS.
- 4.All ferrous parts are hot-dip galvanized.
- 5.All dimensions are in millimeters.
- 6.Applicable standard.(IEC:61284).

8	1	GROUND WIRE	JDX70-2000	AL ALLOY	/
7	1	GROOVE CLAMP	JB-2	AL ALLOY	/
6	1	U-Bolt	U-1680	GAL.V.STEEL	70kN
5	1	EYE CHAIN LINK	ZH-7	GAL.V.STEEL	70kN
4	1	CAST ALLOY CLAMP	TK-7	AL ALLOY	70kN
3	2	RUBBER INSERT	XJ	RUBBER	/
2	1	OUTER PREFORMED	OXY 1200 70-W	AL ALLOY	/
1	1	INNER PREFORMED	OXY 1200 70-N	AL ALLOY	/
ITEM	QTY	DESCRIPTION	TYPE	MATERIAL	Failure load

 Nantong Hongzhi Communication Equipment Co., LTD				
Tolerance		OPGW Suspension clamps TYPE:OXY 1100 70		
$\leq 30\text{mm}$	$\pm 1.5\text{mm}$			
$> 30\text{mm}$	$\pm 5\%$			
MAX.	$\pm 10\text{mm}$			
DRAWING	L.Z.G	DATE:2020-01-10	DRAWING NO.	Version
VERIFY	ZH.J		OXY 1100 70	A
RATIFICATION	ZH.J			